

FICHA TÉCNICA - TECHNICAL SHEET - FICHE TECHNIQUE

DESCRIPCIÓN DEL PRODUCTO - PRODUCT DESCRIPTION - DESCRIPTION PRODUIT

MODELO : NC255200

ENVASE DE ALUMINIO : INTERIOR: Desnudo
EXTERIOR: Desnudo



DIMENSIONES DEL PRODUCTO- PRODUCT DIMENSIONS - DIMENSIONS PRODUIT

DIMENSIONES - dimensions - dimensions

SUPERIOR EXTERIOR - top out - Extérieur supérieur	527x325	mm
SUPERIOR INTERIOR - top in - Intérieur supérieur	497x295	mm
FONDO - bottom - fond	473x271	mm
ALTURA - depth - hauteur	38,1	mm
CAPACIDAD - volume - volume	5200	ml

CARACTERÍSTICAS DEL MATERIAL - MATERIAL SPECIFICATION - SPECIFICATION MATIERE

LUBRICANTE - Lubricant - Lubrifiant	0,5-0,7 g/m2
MATERIAL - material - matiere	Aluminio
ALEACIÓN - alloy - alliage	Serie/s: 5000
ESPESOR - thickness - épaisseur	160 ±8% μ
LACA INTERIOR - lacquering inside- lacque intérieur	g/m2
LACA EXTERIOR - lacquering outside- lacque Extérieur	g/m2

PESO - WEIGHT- POIDS

	Minimum	Nominal	Maximum	
Peso unitario - unit weight - unité de poids	96,69	105,10	113,51	g/container

EMBALAJE - PACKAGING - CONDITIONNEMENT

EMBALAJE PRIMARIO - primary packaging - conditionnement premier	plastic bag
EMBALAJE SECUNDARIO - secondary packaging - conditionnement secondaire	Cardboard
DIMENSIONES - dimensions - dimensions	550x350x550 mm
CAJAS /PALET -boxes / pallet - cartons / palette	12 units
UNIDADES POR CAJA/JAULA- Units per box / cage - unités d'emballage	100 units
CONDICIONES DE ALMACENAJE - Storage conditions - Conditions de stockage	8 - 30 °C, máx. 50% rH

REMARKS: Our acknowledgement presupposes that the packaging material is appropriately processed. Please, be advised that the storage of strongly acidic or alkaline products in direct contact with uncoated aluminium foil should be avoided. In aqueous environment these products can dissolve aluminium, the extent of which would depend on temperature and contact time. The suitability of uncoated aluminium foil for specific applications should be ascertained by the relevant manufacturer / packer.