

FICHA TÉCNICA - TECHNICAL SHEET - FICHE TECHNIQUE

DESCRIPCIÓN DEL PRODUCTO - PRODUCT DESCRIPTION - DESCRIPTION PRODUIT

MODELO : ERA0890

ENVASE DE ALUMINIO : INTERIOR: Desnudo
EXTERIOR: Desnudo



DIMENSIONES DEL PRODUCTO- PRODUCT DIMENSIONS - DIMENSIONS PRODUIT

DIMENSIONES - dimensions - dimensions	
SUPERIOR EXTERIOR - top out - Extérieur supérieur	220x158 mm
FONDO - bottom - fond	174x111 mm
ALTURA - depth - hauteur	36 mm
CAPACIDAD - volume - volume	890 ml

CARACTERÍSTICAS DEL MATERIAL - MATERIAL SPECIFICATION - SPECIFICATION MATIERE

LUBRICANTE - Lubricant - Lubrifiant	0,2-0,5 g/m2
MATERIAL - material - matiere	Aluminio
ALEACIÓN - alloy - alliage	Serie/s: 3000 or 8000
ESPESOR - thickness - épaisseur	70 ±8% μ
LACA INTERIOR - lacquering inside- lacque intérieur	g/m2
LACA EXTERIOR - lacquering outside- lacque Extérieur	g/m2

PESO - WEIGHT- POIDS

	Minimum	Nominal	Maximum	
Peso unitario - unit weight - unité de poids	10,53	11,44	12,36	g/container

EMBALAJE - PACKAGING - CONDITIONNEMENT

EMBALAJE PRIMARIO - primary packaging - conditionnement premiér	BOLSA DE POLIETILENO
EMBALAJE SECUNDARIO - secondary packaging - conditionnement secondaire	CAJA CARTÓN
DIMENSIONES - dimensions - dimensions	CAJA CARTON 530 X 360 X 450 mm
CAJAS /PALET -boxes / pallet - cartons / palette	16 units
UNIDADES POR CAJA/JAULA- Units per box / cage - unités d'emballage	800 units
CONDICIONES DE ALMACENAJE - Storage conditions - Conditions de stockage	8 - 30 °C, máx. 50% rH

REMARKS: Our acknowledgement presupposes that the packaging material is appropriately processed. Please, be advised that the storage of strongly acidic or alkaline products in direct contact with uncoated aluminium foil should be avoided. In aqueous environment these products can dissolve aluminium, the extent of which would depend on temperature and contact time. The suitability of uncoated aluminium foil for specific applications should be ascertained by the relevant manufacturer / packer.

OBSERVACIONES